

CT646FYF Series

From 1.0 μH to 1000 μH



CHARACTERISTICS

- Description:** SMD power inductor.
- Applications:** Ideal for a variety of DC/DC converter applications and low profile use.
- Operating Temperature:** -30°C to +100°C
- Inductance Tolerance:** $\pm 10\%$, $\pm 20\%$
- Testing:** Inductance is tested on an HP4285A at 100KHz.
- Packaging:** Tape & Reel.
- Marking:** Parts are marked with inductance code.
- Miscellaneous:** RoHS Compliant.
- Additional Information:** Additional electrical & physical information available upon request.
- Samples available. See website for ordering information.**

SPECIFICATIONS

Part numbers are marked to indicate tolerance available.

K = $\pm 10\%$, M = $\pm 20\%$

Part Number	Inductance (μH)	L Test Freq. (KHz)	DCR Max. (Ω)	Rated DC (A)
CT646FYF-1R0M	1.0	100	0.023	2.880
CT646FYF-1R5M	1.5	100	0.028	2.560
CT646FYF-2R2M	2.2	100	0.032	2.360
CT646FYF-2R7M	2.7	100	0.035	2.360
CT646FYF-3R3M	3.3	100	0.038	2.160
CT646FYF-3R9M	3.9	100	0.042	2.160
CT646FYF-4R7M	4.7	100	0.049	1.880
CT646FYF-5R6M	5.6	100	0.055	1.880
CT646FYF-6R8M	6.8	100	0.055	1.880
CT646FYF-8R2M	8.2	100	0.067	1.680
CT646FYF-100M	10	100	0.070	1.560
CT646FYF-120M	12	100	0.080	1.440
CT646FYF-150M	15	100	0.090	1.360
CT646FYF-180M	18	100	0.100	1.280
CT646FYF-220M	22	100	0.120	1.170
CT646FYF-270M	27	100	0.140	1.070
CT646FYF-330M	33	100	0.160	1.000
CT646FYF-390M	39	100	0.190	0.910
CT646FYF-470M	47	100	0.220	0.840
CT646FYF-560M	56	100	0.290	0.720
CT646FYF-680M	68	100	0.340	0.660
CT646FYF-820M	82	100	0.460	0.580
CT646FYF-101M	100	100	0.550	0.510
CT646FYF-121K	120	100	0.670	0.420
CT646FYF-151K	150	100	0.900	0.370
CT646FYF-181K	180	100	1.050	0.350
CT646FYF-221K	220	100	1.350	0.290
CT646FYF-271K	270	100	1.550	0.280
CT646FYF-331K	330	100	2.050	0.230
CT646FYF-391K	390	100	2.300	0.215
CT646FYF-471K	470	100	2.600	0.195
CT646FYF-561M	560	100	2.900	0.185
CT646FYF-681M	680	100	3.400	0.170
CT646FYF-821M	820	100	4.200	0.165
CT646FYF-102M	1000	100	5.390	0.150

PHYSICAL DIMENSIONS

Size	A Max.	B Max.	C Max.	D	E Max.
mm	7.4	7.4	5.5	2.0 \pm 0.2	5.4
inches	0.29	0.29	0.22	0.08 \pm 0.008	0.21

