

CTIHLP5026F Series

From 2.2 μH to 22 μH



CHARACTERISTICS

Description: SMD (shielded) power inductor.

Applications: PDA, Notebook, Desktop, Server applications, Low profile, high current power supplies, battery powered devices, DC/DC converter for Field Programmable Gate Array (FPGA).

Operating Temperature: -55°C to +125°C (The part temperature (ambient + temp. rise) should not exceed 125°C under worst case operating conditions. Circuit design, component placement, PWB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application)

Inductance Tolerance: $\pm 20\%$, $\pm 30\%$

Testing: Inductance is tested on an HP4285A at 200KHz, 0.25V, 0A.

Packaging: Tape & Reel.

Marking: Parts are marked with inductance code.

Miscellaneous: **RoHS Compliant.**

Additional Information: Additional electrical & physical information available upon request.

Samples available. See website for ordering information.

SPECIFICATIONS

Please specify tolerance code when ordering.

CTIHLP5026F-2R2 ← M = $\pm 20\%$, N = $\pm 30\%$


*I_{rms} DC current (A) that will cause an approximate ΔT of 40°C.

**I_{sat} DC current (A) that will cause L₀ to drop approximately 20%.

Part Number	Inductance (μH)	L Test Freq. (KHz)	DCR Max. (m Ω)	*I _{rms} Typ. (A)	**I _{sat} Typ. (A)
CTIHLP5026F-2R2_	2.2	200	4.2	20.0	33.0
CTIHLP5026F-3R3_	3.3	200	6.8	15.0	29.0
CTIHLP5026F-4R7_	4.7	200	11.2	13.5	25.0
CTIHLP5026F-5R6_	5.6	200	11.5	12.0	24.0
CTIHLP5026F-6R8_	6.8	200	14.9	11.5	16.5
CTIHLP5026F-8R2_	8.2	200	16.6	10.5	16.0
CTIHLP5026F-100_	10	200	18.5	10.0	15.5
CTIHLP5026F-220_	22	200	45.0	5.0	8.0

PHYSICAL DIMENSIONS

Size	A Max.	B Max.	C Max.	D	E Ref.	F Ref.
mm	13.8	12.9	6.7	4.7 \pm 0.3	8.4	2.4
inches	0.54	0.51	0.26	0.18 \pm 0.012	0.33	0.09



PAD LAYOUT

